

# SKY1016-IV

SKY1016-IV

ASTM D5972 SH/T 0770 IP 435

- iSKvator™
- GB/T 2430 ASTM D2386
- 12
- 0.14mL φ 0.16mL 15
- /
- 
- 
- 
- 
- 5000
- 
- PT100
- 



- 
- 
- 

j

|  |  |                             |  |
|--|--|-----------------------------|--|
|  |  |                             |  |
|  |  | SH/T 0770,ASTM D5972,IP 435 |  |
|  |  | +20,    ϕ -80,              |  |
|  |  | 0.1,                        |  |
|  |  | 0.1,                        |  |
|  |  | 0.5,                        |  |
|  |  | 0.8,                        |  |
|  |  | ϕ 15min                     |  |
|  |  | /                           |  |
|  |  | 15, /min ± 5, /min,         |  |
|  |  | 10, /min ± 0.5, /min        |  |
|  |  | 0.14mL ϕ 0.16mL             |  |
|  |  |                             |  |
|  |  | 12                          |  |
|  |  | 5000                        |  |
|  |  | USB,RJ-45                   |  |
|  |  | LIMS                        |  |
|  |  | 1000W                       |  |
|  |  | 5 ϕ 35,<br>20 ϕ 80% RH      |  |
|  |  | AC220V ± 10% 50Hz           |  |
|  |  | 430mm    Ø510mm    Ø560mm   |  |
|  |  | 37KG                        |  |